

KING RETOOL YOUR METAL SHOP SUMMER 202

TABLE TABLE

POWERFEED

PFM-32

For # PDM-30

MILLING

DRILLING MACHINE STAND SS-45

ATTACHMENT

599

steel construction 5.5 PEAK HP

24 GALLON

6.0 CFM @ 90 PSI

KC-3124V2

AIR COMPRESSOR

2 cylinder cast iron

single stage oil lubricated pump

Proudly Canadian



DVR DRILL PRESS 83705

- Powerful direct drive 1 HP high torque motor with no pulleys or belts to cause vibration
- Spindle taper MT #2/2
 Comes with 5/8" drill chuck
 & key, firmware USB cable,



16" NOVA VIKING 18" NOVA VOYAGER **DVR DRILL PRESS** 58006

- high torque motor with no pulleys or belts to cause vibration Spindle taper MT #2 • Powerful direct drive 1.7
- Comes with 5/8" drill chuck
 key, firmware USB cable knock-out wedge, adjust wrench and hex. keys



7" X 12" METAL CUTTING BANDSAW KC-712BC

- 11.5 Amp. motor Coolant system
- Adjustable ball bearing guides
- 4 speeds (85-130-180-235 FPM)







25'x1/4"

25'x3/8'

\$29.99

\$39.99

\$49.99

\$59.99



99 99

3/4" Bi-Metal 3/4" Bi-Metal KBB-712-BM-610 93" KBB-712-BM-1014 93" ARCTIC FLEX



50'x1/4" K-5014H K-5038H 50'x3/8' K-10014H 100'x1/4" K-10038H 100'x3/8" MAXIMUM PRESSURE

K-2538H

REPAGNETAR FOSE RELIGIOSE ROMERATE FOSE

K-5038FRL

50 ft. x 3/8" All-Weather Flexibility (-40°C to 65°C)
 Comes with wall mounting hardware MANUALAIR LOSI REELWITH HYBRID POLYMERAIR LOSI

KING



• All-Weather Flexibility (-40°C to 65°C)



12" BENCH VARIABLE **SPEED DRILL PRESSES**

KC-12HS-VS

- Powerful 1/2 HP, 5 Amp
- Variable speeds (580 3200 RPM)
 Comes with 5/8" drill chuck, chuck key, onboard chuck key storage and adjustment hex. keys





Mechanical

variable

Since 1983

VV/EIS

15"FLOOR VARIABLE SPEED DRILL PRESSES

KC-15HS-VS

- Powerful 3/4 HP, 8.6 Amp. moto
 4" stroke capacity allows drilling workpieces up to 4" thick
- Variable speeds 2 (280 1100, 900-3300) RPM
- 900-3300) RPM
 Comes with 5/8" drill chuck, chuck
 key, onboard chuck key storage ar
 adjustment hex. keys

16" X 20" COMBO LATHE/MILL KC-1620CLM

• Two powerful 3/4 HP 110V motors

tool box with adjusting tools

- Lathe chuck and drill chuck safety guards with limit switch protection and
- standard tool post safety guard

 Comes with 5"- 3 jaw chuck, imperial & metric change gears, quick change tool post with 1/2" capacity, steady rest, follow rest, thread chasing dial indicator, MT#3 & MT#4 dead centres, 1/2" drill chuck and



OPTIONAL STAND SS-1620CLM (41-3/8" x 19-1/4" x 30-1/2")





WET-DRY VACUUMS

CARTRIDGE FILTER

HEPA (high-efficiency particulate air) filters are designed to capture all particles that are 0.3 microns or smaller.

KVAC-1145 FITS: 8520LP, 8530LPN, 8531LP-B 8540LST



8530LPN

- Powerful 9 Amp.
- 4 Peak HP motor 8 US Gallon (30L) corrosion resistant plastic tank Convenient 12 ft.

power cord Comes complete with 6 ft. x1-1/4" hose, cartridge filter, foam filter, reusable filter, 10" floor sweep and crevice tool



- Powerful 10 Amp
 5 Peak HP motor
- 10 US Gallon (40L) corrosion resistant stainless steel tank
- Convenient 12 ft. power cord

 Comes complete with 6 ft. x 1-1/4" hose, 2 pc. extension wand, 40L dust bag, cartridge filter, foam filter, reusable filter, 10" floor sweep and crevice tool

Shop=vod #906-72



KVAC-1132 FITS: 8530LP, 8531LP-B, 8530LPN, 8540LST S1999

2 cylinder cast iron

single stage oil

lubricated pump

Thermally protected US Motor® 6.5 peak HP moto

Double filtration system with pleated cartridge filter

- Powerful 10.5 Amp., 6.5 Peak HP motor 16 US Gallon (60L) corrosion
- resistant stainless steel tank Convenient 18 ft. power cord



Tank water drain



AIR TOOL KIT 571PG

Comes with 1/2" Impact, Wrench, 3/8" Ratchet Wrench, Air Hammer and 1/4" Die Grinder





AIR COMPRESSORS & ACCESSORIES

TIRE INFLATION GUN WITH PRESSURE **GAUGE**

HP 60 GALLON

KC-6160V3

• 150 PSI max pressure

13.4 CFM @ 40 PSI

11.2 CFM @ 90 PSI

AIR COMPRESSOR



STATIONARY 6.5 PEAK





HIGH OUTPUT 6.5 PEAK

HP 60 GALLON AIR

COMPRESSOR

• 150 PSI max pressure

22.6 CFM @ 40 PSI

18.5 CFM @ 100 PSI

KC-5160V3



3 cylinder cast iron

single stage oil lubricated pump

HIGH OUTPUT 7.5 PEAK HP 80 GALLON AIR COMPRESSOR

KC-7180V3-MS

- 200 PSI max pressure
- 43 CFM @ 40 PSI 28 CFM @ 175 PSI

2 cylinder cast iron

single stage oil lubricated pump

NEW & IMPROVED

High Performance Air Compressor with high output of 28 CFM @ 175 PSI

Θ

SPRAY GUN KITS

8180

8182



8190 HVLP







AIR COMPRESSOR KC-2051H2

- 150 PSI max pressure
- 76 CFM @ 40 PSI

single stage oil ubricated pump







5.5 PEAK HP 20 GALLON

- 6.0 CFM @ 90 PSI

2 cylinder cast iron







2 HP **METAL DUST** COLLECTOR

KC-7300C

- Powerful 2 HP, 220V motor
- · 2 Step activation safety switch with line voltage interruption in case of power failure
- Ideal for collection of metal chips and abrasive dust produced by metal sanders, grinders, cold cut saws, deburring and chamfering machines
- Large metal chips colection drawer is easy to access and clean
- 6" inlet with Y-inlet adaptor with two 3" dust inlets allowing up to connect up to two metalworking machines

FIREPROOF 3"METAL DUST

COLLECTION HOSES KIT 130°

DIGITAL FRACTIONAL CALIPER

• Converts to inches (decimal and fractional) and metric readings

• Comes with large paper filter and iron activated carbon filter



ncludes: 2 - 8f

• Waterproof to IP54 standards

• Two 3V Lithium batteries included

KM-102



MAGNETIC SWITCHES



KMAG-110-811 110V (8-11 Amp.) KMAG-110-1114 110V (11-14 Amp.) KMAG-110-1417 110V (14-17 Amp.) KMAG-220-811 220V (8-11 Amp.) KMAG-220-1114 220V (11-14 Amp.) KMAG-220-1417 220V (14-17 Amp.) KMAG-220-1721 220V (17-21 Amp.)

Comes with Canadian

made 80

Grit pure

10" WET/DRY SHARPENER KIT

KC-4900S

- Heavy-duty 1.6 Amp. motor quietly rotates at 115 RPM for maximum
- precision during sharpening Comes with angle guide honing compound and a square edge jig for sharpening a variety of blades and wood chisels





BENCH GRINDERS

8" LOW SPEED BENCH GRINDER WITH LIGHT

KC-895LS Powerful 1/2 HP, 1,750 RPM motor



BENCH GRINDER STAND

SS-150



3" X 79" METAL BELT SANDER

- Sanding belt rotates on 7-1/2" vented drive wheel and solid rubber rear wheel for maximum tracking and sanding control
- · Head pivots up or down on base for easy and safe work heights
- Horizontal working height of 36"



3"x 79" PURE ZIRCONIA SANDING BELTS

Model	Belt Size	Grit	Unit	Price
SB-379-60	3"x79"	60	1	\$19.99
SB-379-80	3"x79"	80	1	\$19.99
SB-379-120	3"x79"	120	1	\$19.99

zirconia sanding belt KING **2 HP** (220V)

12" HEAVY-DUTY BENCH **GRINDER WITH FLOOR STAND**

KC-1295

Robust cast-iron wheel guards and dust vents with 2-1/2" T-fitting adaptor for dust collection

Comes complete with floor stand, built-in cast-iron quench tray, 36 Grit and

60 Grit 12" x 2" grinding



1.5 HP **Direct Drive** Motor (220V)









KC-1220

- Max. length 12"
- Maximum thickness 20 Gauge
- Weight 95 lbs

KC-3020

- Max. length 30"
- Maximum thickness 20 Gauge
 • Weight 300 lbs



KC-4020

- Max. length 40"
- Maximum thickness 20 Gauge
- Weight 387 lbs



and crimping

\$699.

6% STY

12" HAND SHEAR

KC-HS12

- · Level arm with
- compensating spring
 Easy cutting across the
- entire length
- Rigid cutter body

4 TON HAND NOTCHER

KC-N616

- Heavy cast-iron construction
- 16 Gauge notching capacity (mild steel)
- 18 Gauge piercing capacity (mild steel)
- Maximum notch (6" X 6" x 90°)
- Weight 165 lbs

\$699





SLIP ROLLS

KC-S5016

- Max. length 50"Capacity 16 GaugeWeight 540 lbs

KC-S3622

- Max. length 36"
- Capacity 22 Gauge
- Weight 176 lbs

9 Z/Z/

KC-S2422

- Max. length 24"
- Capacity 22 Gauge
 Weight 81 lbs





FAGOR DIGITAL READOUT SYSTEM



20i-T-840 (Fits KC-1440ML-6 & KC-1440ML-2)

20i-T-1040 (Fits KC-1640ML)





VE CENTERS



KLC-3M TAPER SHANK - MT#3

7 PC. CARBIDE CUTTER HOLDER SETS

• 1/4" Carbide Steel 2 position Cutter Tips (5pcs.)

Carbide Steel Inserts (2pcs.)







Fits Models

Fits Models KC-0712ML, KC-1022ML KC-1236ML, 14440ML-6 KC-1640GH, KC-1640ML KC-1660GH

APER'ATTACHMENT



These Taper Attachments are designed to fit our 12" x 36", 14" x 40" & 16" x 40" Metal Lathes models

KC-1236ML, KC-1440ML-6 & KC-1640ML

PC. QUICK CHANGE



Fits most lathes up to 0 to 12" swing

KQCT-1015 Fits most lathes between 10" to 15" swing

KQCT-1318

Fits most lathes between 13" to 18" swing

METAL LATHES & ACCESSORIES



VARIABLE SPEED MINI METAL LATHE KC-0712ML

- 3/4" spindle bore
- Variable speeds 2 (0-1100, 0-2500 RPM)
- · Comes complete with quick change gear box, face plate, steady rest, replacement gears, 4-way tool post, MT#2 dead center, threading dial indicator, 4"- 3 jaw chuck, emergency stop button, chuck key and hex. keys



KC-1022ML

- 1" spindle bore
- Spindle speeds 6 (150-2400) RPM
- Comes complete with 5"-3 jaw chuck, 6-1/2"-4 jaw chuck, replacement gears, 4 way tool post, steady rest, follow rest, 8" face plate, thread chasing dial indicator, MT#3 dead enter, full length splash guard, tool box, chuck key and hex. keys

2999

GEARHEAD METAL LATHÉ

- 1 1/2" spindle bore
- Spindle speeds 9 (60-1500) RPM
- 40(4-112 T.P.I) 30(.2 4.5mm) thread cutting
- Comes complete with 6"-3 jaw chuck, 8"-4 jaw chuck, imperial and metric gears, quick change tool post, steady rest, follow rest, 10" DI-4 camlock face plate, thread chasing dial indicator, MT#3 dead center, MT#3 arbor taper, 1/2" drill chuck, full length splash guard, tool box, chuck keys and hex. keys

KC-1236ML/SS-1236 KC-1236ML/KM-053/SS-1236

GEARHEAD METAL LATHE

- Spindle speeds 8(70-2000 RPM)
- 34(4-56 T.P.I) 26(.4 7mm) thread cutting
- 2" Spindle Bore Comes complete with 6"-3 jaw chuck, 8"-4 jaw chuck, replacement gears, quick change tool post, steady rest, follow rest, 12" DI-4 camlock face plate, coolant system, full length splash guard, thread chasing dial indicator, 2 MT#3 dead centers, JT#5-MT#3 sleeve, chip tray, tool box, halogen lamp, chuck keys, hex, keys, and cabinet stand with foot brake

KC-1440ML-2

WITH TAPER ATTACHMENT C-1440ML-2/KM-054

1990

HIGH PRECISION "TOOL ROOM" METAL LATHE

- Spindle speeds 16(45-1800 RPM)
- 2" spindle bore diameter
- 45(2-72 T.P.I) thread cutting
- Comes complete with 8"-3 jaw chuck with inside & outside jaws, 12"-4 jaw chuck, quick change tool post and two 3/4" tool holders, steady and follow rests with roller guides, 14" (D1-6) camlock face plate, MT #4 standard dead centre, MT #4 carbide tipped dead centre, MT #4 to MT #6 spindle sleeve adapter, halogen light, coolant system, full length splash guard, manual micrometer carriage


stop, tool box and wrenches

39)

KC-1640ML

WITH TAPER ATTACHMENT KC-1640ML/KM-055

5990





























METAL CUTTING BANDSAWS





10" x 18" 111:5/Amp@220V

Model

KBB-225-10 122ⁿ

KBB-225-14 122

METAL CUTTING BANDSAW

KC-227-2 (220V)

- KC-227-6 (600V)

 4 speeds (114, 196, 288, 377 FPM)

 Carbide ball bearing blade guide

 Centralized control panel and automatic shut-off
- Adjustable hydraulic downfeed control
- To ensure reliable accurate cuts, both adjustable control arms can be positioned as close to the cut as possible



H.S.S. BLADES

10 .032"

14 .032

TPI Thickness

Price

\$35.99


Length Width

VARIABLE SPEED SWIVEL METAL CUTTING BANDSAW

KC-228S-V-2 (220V) KC-228S-V-6 (600V)

• Variable Speeds (73-312 FPM)

• Carbide ball bearing blade guides Adjustable hydraulic







METAL CUTTING BANDSAWS

PATENTED GEAR DRIVE SYSTEM...

is the ONLY one in the Canadian market which allows the user to change speeds without stopping the machine.

METAL CUTTING BANDSAW WITH GEAR DRIVE

KC-712GH-5

- Returning coolant system3(110-230-340 FPM)
- Automatic shut-off
- Adjustable ball bearing guides



9"x 18"

METAL CUTTING SWIVEL BANDSAW

KC-918S-V

- Returning coolant system
- Speeds (80-250 FPM)
- Carbide ball bearing blade guides with rollers
- · Centralized control panel and automatic shut-off
- Adjustable hydraulic downfeed control
- Precision blade tension adjustment
- Head swivels 0° to 45° in one direction
- Quick-positioning vise with fully adjustable jaws for 0° to 45° angles



DUAL SWIVEL METAL CUTTING BANDSAW

KC-712DS

- Returning coolant system
- 4 speeds (98-164-246-328 FPM)
- Automatic shut-off



VARIABLE SPEED METAL/WOOD CUTTING BANDSAW

KC-1700WM-VS

- Variable speeds (wood): 540-3600 SFPM
 Variable speeds (metal): 100-650 SFPM
 Voltage (input power): 220V, 1 phase, 60 Hz
 Comes with a 1/2" x 6 TPI wood cutting blade, 1/2" x 10 TPI metal cutting blade, laser guide, work la work lamp, miter gauge and a precision "TRU-RIP" aluminum rip fence with resaw guide

18"

METAL CUTTING BANDSAW

KC-450

- Variable speedHandwheel controls speed
- Speed changes while the
- machine is in operation
 Comes complete with 4-way tilting table, and work light

0 0



5100W GASOLINE GENERATOR WITH WHEEL KIT

- KCG-5100G
 Powerful 8 HP, 4 stroke air cooled OHV engine
- AVR system and electronic ignition
 Low oil shut-off with indicator light protects the engine
- Duplex outlet: 120V/20 Amp. AC
- Twist lock outlet: 120V/240V/30 Amp. AC
- · AC double throw circuit breaker and resets
- CSA & EPA approved



6500W GASOLINE GENERATOR WITH ELECTRIC START

- KCG-6502GE
 Powerful 10 HP, 4 stroke air cooled motor
- AVR system and electronic ignition
 Low oil shut-off with indicator light protects the engine
 Duplex outlet: 120V/20 Amp. AC
- Twist lock outlet: 120V/240V/30 Amp. AC
- · AC double throw circuit breaker and resets for safe operation
- CSA & EPA approved







KCG-1501GX • Powerful 3 HP, 4 stroke air cooled OHV engine • Electronic ignition

1800W GASOLINE GENERATOR

- · Low oil shut-off with indicator light protects the engine
- Duplex Outlet: 120V/11.6 Amp. AC output
- Terminals: 12V, 8 Amp. DC output
 AC and DC circuit breakers for safe operation
- Comes with DC cables and spark plug socket
- · Easy start recoil starter
- CSÁ & EPA approved



12000W GASOLINE **GENERATOR WITH ELECTRIC START**

KCG-12000GE

- Powerful 18 HP, 4 stroke air cooled motor
- AVR system and electronic ignition
- · Low oil shut-off with indicator light protects the engine
- Two duplex outlets: 120V/20 Amp. AC
- Twist lock outlet: 120V/240V/30 Amp. AC
- Outlet: 120V/240V/50 Amp. AC
- Keyed electric start and easy start recoil starter
- AC double throw circuit breaker and resets



12000W DUAL/FUEL **GASOLINE/PROPANE GENERATOR**

WITH ELECTRIC START

KCG-12001GE-DF

- Powerful 18 HP 4 stroke air cooled motor
- AVR system and electronic ignition
- · Low oil shut-off with indicator light protects the engine
- Two duplex outlets: 120V/20 Amp. AC
- Twist lock outlet: 120V/240V/30 Amp. AC
- Outlet: 120V/240V/50 Amp. AC
- Keyed electric start and easy start recoil starter
- · AC double throw circuit breaker and resets

Comes with propane tank connection cable



PORTABLE & GASOLINE GENERATORS & ACCESSORIES WITH ELECTRIC START

KCG-10001GE

- Powerful 15 HP, 4 stroke air cooled motor
- AVR system and electronic ignition
 Low oil shut-off with indicator light protects the engine
 Two duplex outlets: 120V/20 Amp. AC
 Two twist lock outlets: 120V/30 Amp and 120V/240V/30 Amp AC
- Keyed electric start and easy start recoil starter
 AC double throw circuit breaker and resets for safe operation
- CSA & EPA approved



2000W GASOLINE DIGITAL INVERTER GENERATOR



 Sine wave digital inverter generator provides stable current to power voltage-sentitive electronics Powerful 3 HP, 4 stroke air cooled

OHV engine DC output for charging smartphones, tablettes or any USB powered equipment

 DC Cigarette Lighter Socket: 12V/8 Amp DC output
 AC Duplex Outlet: 120V/ 13.3 Amp AC output



Parallel Cable Kit for connectivity between two inverters



USB**a**n

USB**a**s

4000W GASOLINE DIGITAL INVERTER GENERATOR

KCG-4000i

- Sine wave digital inverter generator provides stable current to power voltage-sensitive electronics
- DC USB port: 5V/2.1 Amp.
- DC cigarette lighter socket: 12V/8 Amp. DC output
- AC duplex outlet: 120V/20 Amp. AC output
 AC twist lock outlet: 120V/30 Amp. AC output



Powerful 7.5 HP, 4 stroke air cooled OHV engine



GENERATOR EXTENSION CORDS

K-L1430-10 Extension cord length: 10 feet Gauge (AWG)/Cord:

K-L1430R-25

Extension cord length: 25 feet Gauge (AWG)/Cord: 10 (SJTW 4/C) Resets

Gauge (AWG)/Cord: 10 (SJTW 4/C) Lighte Lighted

Extension cord length:

25 feet

Converts a Nema L14-30P 240V 30 Amp Twist Lock plug into Nema 5-15/20R 120V 20A receptacles K-L1430-25-4T K-L1430-25EXT

Extension cord length 25 feet Gauge (AWG)/Cord 10 (SJTW 4/C)



50 AMP. GENERATOR **ADAPTOR CORD**

K-1450P-2

1.5 feet Gauge (AWG)/Cord: 10 (SJTW 4/C)

Nema 14-50P 120/240V plug to Nema L14-30R 120/240V twist lock receptacle





Outdoor to indoor receptacle kit

es with 6 outlet power panel, generator power inlet box, ' rigid PVC conduit, 1-1/4" spade bit, 1/2" PVC sleeve ector, 2 insulating gaskets and mounting hardware



PORTABLE VARIABLE SPEED **METAL CUTTING BANDSAW**

KC-8377

- Variable speed dial for 0-420 SFPM
- Cutting capacity of 5" x 5"
 Blade tension lever for
- quick adjustments
- Comes with standard 44-7/8" x 1/2" x 0.025"-14 TPI metal cutting blade

Optional

Miter Stand turns this Bandsaw into a Cut-off Saw

SS-8377

8342LN



CUT-OFF SAW

• Large trigger switch in handle for safe and easy use

• Spark deflector for safe operation

• Large handle facilitates transport

PALLET

(21" X 45")

(27" X 48")

Nylon wheels

Nylon wheels

TRUCKS KC-2145N-NYL

· Heavy-duty steel base with foot pads minimizes vibration

• Quick release vise for holding workpiece, which allow cuts up to a 45° angle

· Onboard abrasive wheel wrench storage

Powerful 15 Amp motor

• Standard 14" abrasive wheel for cutting ferrous metal



H.S.S. BLADES								
Model	Length	Width	TPI	Thickness	Price			
KBB-8376-BM-1014	44 7/8"	1/2"	10-14	.020"	\$19.99			
KBB-8376-BM-1418	44 7/8"	1"	14-18	.020"	\$19.99			

15,000W V-TWIN GASOLINE GENERATOR WITH ELECTRIC START

KCG-15000GE

- AVR system and electronic ignition
- Two duplex outlets: 120V/20 Amp. AC Twist lock outlet: 120V/30 Amp. AC
- Outlet: 120V/240V/50 Amp. AC
- AC double throw circuit breaker and resets
 Terminals: 12V/8.3 Amp. DC with DC reset
- CSA & EPA approved

Powerful 20 HP. V-Twin horizontal shaft 4 stroke air cooled OHV engine

AUTO-IDLE DOWN **FUNCTION**



3000 PSI GASOLINE HIGH PRESSURE WASHER

KPW-3001FM

- 3000 PSI, 2.3 GPM maximum water flow
- Thermal relief valve on pump to
- protect against overheating
 25' high pressure hose and inlet





INE WATER PU

• 105' (KCG-2WPG) or 92' (KCG-3WPG) total head lift (total height at sea level, to which water can be raised above original water level)

Powerful 7 HP, 4 stroke air cooled OHV engine

AC

3 postion control handle

Max raised height

of forks 7,1/2"



Comes with 3 wire clamps, 2 hose adapters, 2 rubber gaskets, strainer basket and strainer basket adapter

Powerful 7 HP. 4 stroke air o





Standard







WATER PUMP HOSE KITS

Each hose kit comes with a type A threaded camlock adaptor

SUCTION HOSES

FLAT PVC DISCHARGE HOSES



KW-252

2" X 25 ft

KW-253 3" X 25 ft KW-502 KW-503 2" X 50 ft 3" X 50 ft

GASOLINE ENGINES

• Ideal for compressors, generators, pressure washers, go-karts and log splitters

Counterclockwise drive shaft direction KCG-65









